



### Main

Range of product	Unica
Range	Unica
Device application	Control
Product or component type	Switch
Aesthetic name	Unica Top - Unica Class
Device presentation	Mechanism
Switch function	2-way
Switch application	Roller blind
Rated current	10 A, 250 V AC, 50/60 Hz
Actuator	Rocker
Number of modules	2 modules
Fixing mode	Screws
Cover plate colour tint	Graphite

### Complementary

Number of poles	1
Contacts type and composition	1 C/O
Mechanical interlocking	Interlock between up/down
[I <sub>u</sub> ] rated interrupted current	Motor : 2.5 A
Opening distance	> 3 mm
Marking	UP Down
Connections - terminals	Screwless terminals
Cable cross section	<= 2.5 mm <sup>2</sup> (flexible) <= 2.5 mm <sup>2</sup> (rigid)
Minimum load breaking capacity	200 operations 1.25 I <sub>n</sub> and 1.1 I <sub>un</sub> , cos phi: 0.3
Electrical durability	40000 cycles (cos phi: 0.6)
Insulation resistance	> 5 MOhm @500 V

Dielectric strength	> 2000 V
Material	Fixing frame : zamak Mechanism cover : ABS (acrylonitrile butadiene-styrene)
Standards	EMC directive EN 60669-1 LV directive
Product certifications	FR.ME63.B02736
Ambient air temperature for operation	25...35 °C
Ambient air temperature for storage	0...50 °C
Embedding depth	22 mm
Depth	34 mm
Width	70.9 mm
Height	70.9 mm
Product weight	0.073 kg
Market segment	Residential Small commercial

## Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Oil UV resistant Window-cleaning fluid Acetone Alcohol Ammonia Liquid soap Petrol Bleach
Environmental health and issues	Halogen free

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0702 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------