



Main

Range of product	Unica
Range	Unica
Device application	Control
Product or component type	Cord push-button switch
Aesthetic name	Unica Top - Unica Class
Device presentation	Mechanism with zamak fixing frame
Switch function	Push-button
Rated current	10 A, 250 V AC, 50/60 Hz
Actuator	Cord push-button
Number of modules	2 modules
Fixing mode	Screws
Colour tint	Graphite

Complementary

Cable length	1 m
Load current	10 A
Opening distance	> 3 mm
Connections - terminals	Screwless terminals
Cable cross section	2.5 mm ² (flexible) 2.5 mm ² (rigid)
Minimum load breaking capacity	200 operations 1.25 I _n and 1.1 I _{un} , cos phi: 0.3
Electrical durability	40000 cycles (cos phi: 0.6)
Insulation resistance	> 5 MOhm @500 V
Dielectric strength	> 2000 V
Material	Fixing frame : zamak Mechanism cover : ABS (acrylonitrile butadiene-styrene)
Standards	EN 60669-1 EMC directive

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

	LV directive
Product certifications	FR.ME63.B02736
Ambient air temperature for operation	25...35 °C
Ambient air temperature for storage	0...50 °C
Embedding depth	22 mm
Depth	34 mm
Width	70.9 mm
Height	70.9 mm
Product weight	0.0636 kg
Market segment	Residential Small commercial
Surface finish	Brilliant

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Liquid soap Petrol Alcohol Oil Bleach Ammonia UV resistant Acetone Window-cleaning fluid
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0622 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------