



Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica (standard aesthetic)
Product or component type	RJ45 connector
Device presentation	Mechanism with zamak fixing frame
Colour tint	White (RAL 9003)
Data socket type	RJ45 - 8 contacts - category 6 - transmission rate < 250 MHz
Provided equipment	Label holder Protective flap

Complementary

Communication network type	1000BASE-TX
Communication port protocol	ATM 1200 Mbps
Number of modules	2 modules
Socket number	1
Type of footprint	Infraplus
Connector type	S-One
Cable shielding type	U/UTP
Organization of wire	Unshielded twisted pair
Connections - terminals	Click
Fixing mode	Screws
Material	Mechanism cover : ASA + PC Fixing frame : zamak
Depth	36 mm
Width	70.9 mm
Height	70.9 mm
Embedding depth	25 mm

Environment

IP degree of protection	IP40
IK degree of protection	IK01

MGU5.415

Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free
Standards	ISO 8877

Contractual warranty

Warranty period	18 months
-----------------	-----------