



Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	TV/FM/SAT socket
Device presentation	Mechanism with zamak fixing frame
TV socket type	TV/FM/SAT
Colour tint	Graphite

Complementary

TV connector	Male IEC 9.52 mm
Radio connector	Female IEC 9.52 mm
SAT connector	F type
Path attenuation	TV : 1.5 dB @10...68 kHz TV : 1.5 dB @140...862 kHz FM : 2 dB @87.5...125 kHz SAT : 3 dB @950...2150 kHz
DC current flow	In SAT socket
Number of modules	2 modules
Material	Insert : zinc alloy Centre plate : thermoplastic ABS-UV stabilised Support frame : PBT (polybutylene terephthalate) GF30
Fixing mode	Without claws
Depth	35 mm
Width	74.9 mm
Height	74.9 mm
Embedding depth	20 mm
Product weight	0.088 kg

MGU5.450

Environment

IP degree of protection	IP20
IK degree of protection	IK02
Ambient air temperature for operation	5...45 °C
Ambient air temperature for storage	-5...50 °C
Environmental characteristic	Window-cleaning fluid UV resistant Ammonia Acetone Oil Alcohol Liquid soap Petrol Bleach
Environmental health and issues	Halogen free
Standards	EN 50083

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0852 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------