



Main

Range	Unica
Range of product	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	TV/FM socket
Device application	Media device support
Device presentation	Mechanism with fixing frame and central plate
TV socket type	End-of-line (terminal socket)
Colour tint	Graphite

Complementary

TV connector	Male IEC 9.52 mm
Radio connector	Female IEC 9.52 mm
Device composition	Support ring
Path attenuation	TV/UHF : 13.5 dB @125...860 MHz TV/VHF : 13.5 dB @47...68 MHz R : 27 dB @87.5...108 MHz
DC current flow	Yes
Number per line	1
Number of modules	2 modules
Material	Mechanism cover : ASA + PC Fixing frame : zamak
Surface finish	Brilliant
Condition of use	Parallel distribution systems
Marking	With imprint
Device mounting	Flush
Fixing mode	Screws
Depth	28 mm
Width	70.9 mm

Height	70.9 mm
Embedding depth	18 mm
Product weight	0.108 kg
Market segment	Small commercial Residential

Environment

IP degree of protection	IP20
IK degree of protection	IK01
Ambient air temperature for operation	15...35 °C
Ambient air temperature for storage	0...35 °C
Environmental characteristic	Liquid soap Oil Alcohol Bleach UV resistant Petrol Window-cleaning fluid Acetone Ammonia
Environmental health and issues	Halogen free
Standards	EMC directive EN 50083-2 EN 50083-4 EN 50083-1

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0702 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------