



### Main

Range	Unica
Range of product	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	R-TV/SAT socket
Device application	Media device support
Device presentation	Mechanism with fixing frame and central plate
TV socket type	Intermediate socket (passage)
Colour tint	Graphite

### Complementary

TV connector	Male IEC 9.52 mm
SAT connector	Female IEC 9.52 mm
Device composition	Support ring
Branch attenuation	TV : 1 dB SAT : 1.5 dB
Path attenuation	SAT : < 12 dB @950...2400 MHz R : 13 dB @10...108 MHz TV/UHF : 13 dB @470...830 MHz TV/VHF : 13 dB @118...470 MHz
DC current flow	In SAT socket
Number per line	4
Number of modules	2 modules
Material	Mechanism cover : ASA + PC Fixing frame : zamak
Surface finish	Brilliant
Condition of use	Series distribution systems
Marking	With imprint
Device mounting	Flush
Fixing mode	Screws

Depth	28 mm
Width	70.9 mm
Height	70.9 mm
Embedding depth	18 mm
Product weight	0.108 kg
Market segment	Small commercial Residential

## Environment

IP degree of protection	IP20
IK degree of protection	IK01
Ambient air temperature for operation	15...35 °C
Ambient air temperature for storage	0...35 °C
Environmental characteristic	Alcohol Ammonia Liquid soap Acetone Bleach Petrol Window-cleaning fluid UV resistant Oil
Environmental health and issues	Halogen free
Standards	EN 50083-1 R.D. 279/1999 EN 50083-4 DIN 45330 DIN 45325 EMC directive UNE 20-523-79 (2e) R.D. 1/1998 EN 50083-2

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0803 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------