



Main

Range	Unica
Range of product	Unica
Product or component type	SAT single shield
Device mounting	Flush
Device presentation	Mechanism with fixing frame and central plate
Colour tint	Graphite
Quantity per set	Set of 10
Sale per indivisible quantity	1

Complementary

SAT connector	F type
Device composition	Support ring
Branch attenuation	1.5 dB signal for SAT - frequency limit: 950...2150 MHz
Connections - terminals	Screw
Shape of screw head	Pozidriv No 1
Wire stripping length	8 mm
Type of cable	Coaxial
Cable outer diameter	7 mm
Fixing mode	By screws
Material	Centre plate : ASA + PC Support cover : PA6 GF30 Casing : zinc alloy Fixing frame : zinc alloy
Surface finish	Brilliant
Type of packing	Flow-pack and cardboard with eurohole
Depth	34.1 mm
Width	71 mm
Height	71 mm
Embedding depth	18.1 mm
Product weight	0.08 kg

MGU5.488

Environment

IP degree of protection	IP20
IK degree of protection	IK04
Ambient air temperature for operation	5...45 °C
Ambient air temperature for storage	-5...50 °C
Environmental characteristic	Alcohol Ammonia Acetone UV resistant Petrol Window-cleaning fluid Oil Liquid soap Bleach
Environmental health and issues	Halogen free
Standards	EN 50083-4 2006/95/EC