



Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	Telephone socket
Device presentation	Mechanism with zamak fixing frame
Colour tint	Graphite
Telephone socket type	RJ12 (6 contacts): cat.3 (rate: 16 Mbit/s)

Complementary

Socket number	1
Number of modules	2 modules
Connections - terminals	Screwless terminals (twisted pair)
Fixing mode	Pins
Material	Fixing frame : zamak Mechanism cover : ABS (acrylonitrile butadiene-styrene)
Depth	36 mm
Width	70.9 mm
Height	70.9 mm
Embedding depth	26 mm
Product weight	0.048 kg
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Market segment	Residential Small commercial

Environment

IP degree of protection	IP20
-------------------------	------

MGU5.493

IK degree of protection	IK01
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0702 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------