



### Main

Range of product	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	Rotary dimmer
Device presentation	Mechanism with zamak fixing frame
Fixing mode	Screws
Dimmer application	Resistive load Inductive load
[Ue] rated operational voltage	230 V AC, 50 Hz
Number of modules	2 modules
Cover plate colour tint	Graphite

### Complementary

Dimmer control	270° rotary setting ON/OFF push
Maximum permanent current	1.74 A
Total number of wires	2
Load type	230 V AC halogen lamp - 40...400 W 230 V AC incandescent lamp - 40...400 W Low voltage halogen lamp with ferromagnetic transformer - 40...400 VA
Protection type	Fuse protection
Fuse type	4 Ah (5 x 20 mm) @230 V 50 Hz
Marking	L+N
Connections - terminals	Screw terminals
Clamping connection capacity	<= 2 x 2.5 mm <sup>2</sup> for flexible cable(s) <= 2 x 2.5 mm <sup>2</sup> for rigid cable(s)
Connected auxiliaries	2-way switch
Material	Mechanism cover : ASA + PC Fixing frame : zamak
Standards	EN 60669-2-1
Product certifications	CE
Ambient air temperature for operation	5...30 °C
Ambient air temperature for storage	-20...60 °C
Embedding depth	34 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Depth	54 mm
Width	70.9 mm
Height	70.9 mm
Product weight	0.1055 kg
Market segment	Small commercial Residential

## Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Bleach Alcohol Acetone Liquid soap UV resistant Petrol Ammonia Window-cleaning fluid Oil
Environmental health and issues	Halogen free

## Contractual warranty

Warranty period	18 months
-----------------	-----------