



Main

Range of product	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	Rotary dimmer
Device presentation	Mechanism with zamak fixing frame + long claws
Fixing mode	Long claws
Dimmer application	Resistive load Inductive load Motor
[Ue] rated operational voltage	230 V AC, 50 Hz
Number of modules	2 modules
Cover plate colour tint	Graphite

Complementary

Dimmer control	ON/OFF push
Maximum permanent current	2.6 A
Total number of wires	3
Load type	230 V AC halogen lamp - 40...1000 W 230 V AC incandescent lamp - 40...1000 W Low voltage halogen lamp with ferromagnetic transformer - 40...1000 VA 230 V AC motor - 60...600 W
Protection type	Electronic overvoltage protection Current protection
Marking	L+N
Connections - terminals	Screw terminals
Clamping connection capacity	<= 2 x 2.5 mm ² for flexible cable(s) <= 2 x 2.5 mm ² for rigid cable(s)
Material	Mechanism cover : ASA + PC Fixing frame : zamak
Standards	EN 60669-2-1
Product certifications	Aenor CE
Ambient air temperature for operation	5...30 °C
Ambient air temperature for storage	-20...60 °C
Embedding depth	34 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Depth	54 mm
Width	70.9 mm
Height	70.9 mm
Product weight	0.1251 kg
Market segment	Residential Small commercial

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Window-cleaning fluid Ammonia Alcohol Acetone Oil Liquid soap Petrol Bleach UV resistant
Environmental health and issues	Halogen free

Contractual warranty

Warranty period	18 months
-----------------	-----------