



Main

| | |
|---------------------------|-----------------------------------|
| Range of product | Unica |
| Range | Unica |
| Aesthetic name | Unica KNX |
| Device application | Control |
| Product or component type | Switch |
| Device presentation | Mechanism with zamak fixing frame |
| Bus type | KNX |
| Switch function | 1-pole 2-way |
| Colour tint | Graphite |

Complementary

| | |
|---------------------------------------|---|
| Rated current | 10 A, 24 V DC |
| Insulation resistance | > 5 MOhm @500 V |
| Dielectric strength | 2000 V |
| Actuator | Push-button |
| Number of modules | 2 modules |
| Pilot light | Blue LED : 1 mA (temperature : 15 °C) |
| Connections - terminals | Screwless terminals |
| Cable cross section | 0...2.5 mm ² (rigid) 0...2.5 mm ² (flexible) |
| Material | Plastic |
| Surface finish | Varnished |
| Device mounting | Flush |
| Fixing mode | Screws |
| Depth | 38 mm |
| Embedding depth | 13 mm |
| Ambient air temperature for operation | -5...45 °C |
| Standards | LV directive |

Environment

| | |
|---------------------------------|--|
| IP degree of protection | IP20 |
| Environmental characteristic | Bleach Ammonia Window-cleaning fluid UV resistant Oil Alcohol Liquid soap Petrol Acetone |
| Environmental health and issues | Halogen free |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1342 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available Product environmental |
| Product end of life instructions | Available End of life manual |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|