



Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica KNX
Product or component type	Movement detector
Device presentation	Mechanism with zamak fixing frame
Cover plate colour tint	Graphite

Complementary

[Ue] rated operational voltage	230 V AC (+/- 10 %), 50/60 Hz
Movement detection area	9 x 9 m (PIR mounting height 2.15m)
Detection angle	Full 180°
Number of modules	2 modules
Light intensity adjustment	10...< 1000 lux @rotary switch 10...2000 lux @ETS
Time delay range	1 s...8 min for rotary switch 1 s...255 h for ETS
Clamping connection capacity	<= 2 x 2.5 mm ² for flexible cable(s) <= 2 x 2.5 mm ² for rigid cable(s)
Connections - terminals	Screwless terminals
Material	Mechanism cover : ASA + PC Fixing frame : zamak
Fixing mode	Claws
Mounting height	1...2.5 m
Depth	56 mm
Embedding depth	34 mm
Market segment	Small commercial

Environment

IP degree of protection	IP20
Ambient air temperature for operation	-5...45 °C
Environmental characteristic	Liquid soap Petrol Bleach

Window-cleaning fluid
UV resistant
Ammonia
Alcohol
Acetone
Oil

Environmental health and issues	Halogen free
Standards	EMC directive LV directive

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0852 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
------------------------	---

Contractual warranty

Warranty period	18 months
-----------------	-----------
