



Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	Time delayed key card switch
Device application	Control
Device presentation	Mechanism with zamak fixing frame
Cover plate colour tint	Graphite

Complementary

[Ue] rated operational voltage	230 V +/- 10 % AC 50 Hz
Rated current	8 A
Load type	230 V AC incandescent lamp - 1470 W 230 V AC halogen lamp - 1470 W 230 V AC fan - 1470 W 230 V AC convector - 1470 W Low voltage halogen lamp with ferromagnetic transformer - 1000 VA Low voltage halogen lamp with electronic transformer - 1470 VA Fluorescent tube ferromagnetic ballast - 1470 VA Compact fluorescent lamp - 1470 W LED lamp - 1470 W Contactor
Actuator	Card 54 x 86 x 0.85 mm (maximum)
Number of modules	2 modules
Fuse type	Electronic
Maximum number of switchings	50000 operations
Protection type	Overvoltage protection Thermal protection
Pilot light	Amber indicator lamp
Time delay	Adjustable between 10 s and 3 mn
Marking	Vertical insertion pictogram
Connections - terminals	Screw terminals
Clamping connection capacity	<= 2 x 2.5 mm ² for flexible cable(s) <= 2 x 2.5 mm ² for rigid cable(s)
Fixing mode	Screws Claws

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Material	Mechanism cover : ASA + PC Fixing frame : zamak
Embedding depth	14 mm
Depth	Unica Top cover frame : 35 mm Unica Class cover frame : 35 mm
Width	70.9 mm
Height	70.9 mm
Product weight	0.0795 kg
Market segment	Residential Small commercial

Environment

IP degree of protection	IP20
IK degree of protection	IK01
Ambient air temperature for operation	5...30 °C
Ambient air temperature for storage	-20...60 °C
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free
Product certifications	FR ME63 B02736
Standards	EN 60669-1

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0702 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------