



Main

Range of product	Unica Wireless
Product or component type	Combined relay
Device presentation	Mechanism with zamak fixing frame + long claws
Transmission frequency	868.3 MHz
[Ue] rated operational voltage	110/230 V AC (+/- 10 %), 50/60 Hz
Number of modules	2 modules
Fixing mode	Claws
Colour tint	White
Device composition	Wireless emitter and receiver 1 large rocker and 2 narrow rockers
Provided equipment	Set of 8 symbols

Complementary

Wiring device mounting	Flush
Operating distance	Indoor : 10...50 m Outdoor : <= 300 m
Load type	Fluorescent tube (diameter: 28...38 mm) : 1 1-10 V dimmable electronic ballast - 920 VA 230 V AC incandescent lamp - 2300 W 230 V AC halogen lamp - 2000 W 230 V AC compact fluorescent lamp - 880 VA 230 V AC fan - 690 W 230 V AC LED lamp - 880 W Low voltage halogen lamp with electronic transformer - 500 VA Low voltage halogen lamp with ferromagnetic transformer - 500 VA Low voltage halogen lamp with toroidal transformer - 500 VA Motor - 690 W
Protection type	Fuse protection
Connections - terminals	Screw terminals
Clamping connection capacity	<= 2 x 2.5 mm ² for flexible cable(s) <= 2 x 2.5 mm ² for rigid cable(s)
Type of setting	Neutral position

Standards	EN 61000-6-3 89/336/EEC 99/5/EEC EN 61000-6-2 ETSI EN 301 489 ETSI EN 300 220 EN 60669-1 EN 60669-2-1 73/23/EEC
Ambient air temperature for operation	-5...50 °C
Relative humidity	20...95 %
Embedding depth	34 mm
Depth	46 mm
Market segment	Residential Small commercial

Environment

IP degree of protection	IP20
Environmental characteristic	Window-cleaning fluid Alcohol Liquid soap Ammonia UV resistant Petrol Acetone Bleach Oil
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1426 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------