



Main

Range of product	Unica Wireless
Product or component type	Combined dimmer
Device presentation	Mechanism with zamak fixing frame + long claws
Transmission frequency	868.3 MHz
[Ue] rated operational voltage	230 V AC (+/- 10 %), 50 Hz
Number of modules	2 modules
Fixing mode	By claws
Colour tint	Graphite
Device composition	1 large rocker and 2 narrow rockers Wireless emitter and receiver
Provided equipment	Set of 8 symbols

Complementary

Wiring device mounting	Flush
Type of setting	Without neutral position
Operating distance	Indoor : 10...50 m Outdoor : <= 300 m
Load type	230 V AC halogen lamp - 20...315 W 230 V AC incandescent lamp - 20...315 W Low voltage halogen lamp with electronic transformer - 20...315 VA Low voltage halogen lamp with ferromagnetic transformer - 20...315 VA Low voltage halogen lamp with toroidal transformer - 20...270 VA
Protection type	Temperature rise protection Overload protection Damage protection from inappropriate load Short-circuit protection
Connections - terminals	Screw terminals
Clamping connection capacity	<= 2 x 2.5 mm ² for flexible cable(s) <= 2 x 2.5 mm ² for rigid cable(s)
Standards	EN 60669-1 EN 60669-2-1 ETSI EN 300 220 73/23/EEC EN 61000-6-3 89/336/EEC 99/5/EEC

ETSI EN 301 489
EN 61000-6-2

Ambient air temperature for operation	-5...35 °C
Relative humidity	20...95 %
Embedding depth	34 mm
Depth	46 mm

Environment

IP degree of protection	IP20
Environmental characteristic	Ammonia Bleach Liquid soap UV resistant Petrol Window-cleaning fluid Alcohol Acetone Oil
Environmental health and issues	Halogen free

Offer Sustainability

RoHS (date code: YYWW)	Will be compliant on 1Q2016 Will be compliant on 1Q2016
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------