



Main

Range of product	Unica
Range	Unica
Device application	Signalling
Product or component type	Electronic bell
Aesthetic name	Unica Top - Unica Class
Device presentation	Mechanism with zamak fixing frame
[Ue] rated operational voltage	230 V AC, 50/60 Hz
Number of modules	2 modules
Fixing mode	Screws
Colour tint	Graphite
Market segment	Residential Small commercial

Complementary

Current consumption	14 mA
Type of setting	5 programmable melodies
Device mounting	Flush
Connections - terminals	Screw terminals
Acoustic level	70 dB/1m
Cable cross section	0.75...1.5 mm ² (flexible) 0.75...1.5 mm ² (rigid)
Connected auxiliaries	10 standard push-buttons connected in parallel 3 indicator lights connected in parallel
Material	Mechanism cover : ASA + PC Fixing frame : zamak
Standards	IEC 62080
Product certifications	CE
Ambient air temperature for operation	15...30 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient air temperature for storage	0...35 °C
Embedding depth	33 mm
Depth	44 mm
Width	45 mm
Height	45 mm
Product weight	0.149 kg

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Oil Bleach Alcohol UV resistant Petrol Ammonia Acetone Window-cleaning fluid Liquid soap
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0852 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------