



Main

Range of product	Unica
Range	Unica
Accessory / separate part category	Cabling accessory
Product or component type	Cable outlet
Aesthetic name	Unica Top - Unica Class
Device presentation	Mechanism with zamak fixing frame
Number of modules	2 modules
Fixing mode	Screws
Provided equipment	Anti-tug clamps
Colour tint	Graphite

Complementary

Range compatibility	Unica
Rated current	16 A
Connections - terminals	Screw terminals
Clamping connection capacity	<= 3 x 2.5 mm ² for flexible cable(s) <= 3 x 2.5 mm ² for rigid cable(s)
Material	Mechanism cover : ASA + PC Fixing frame : zamak
Product certifications	ES.ME01.B02319 AC
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Width	70.9 mm
Height	70.9 mm
Product weight	0.052 kg

Environment

IK degree of protection	IK01
IP degree of protection	IP40
Environmental characteristic	UV resistant Liquid soap Alcohol

Ammonia
Oil
Bleach
Acetone
Window-cleaning fluid
Petrol

Environmental health and issues	Halogen free
---------------------------------	--------------

Contractual warranty

Warranty period	18 months
-----------------	-----------
