



## Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	Loudspeaker socket
Device application	Media device support
Device presentation	Mechanism with zamak fixing frame
Colour tint	Graphite

## Complementary

Socket number	2
Number of modules	2 x 1 module
Connections - terminals	4 : pressure fixing
Fixing mode	Clip-in
Material	Mechanism cover : ASA + PC Fixing frame : zamak
Surface finish	Brilliant
Depth	37 mm
Width	45 mm
Height	45 mm
Product weight	0.063 kg
Market segment	Small commercial Residential

## Environment

IP degree of protection	IP20
IK degree of protection	IK01
Ambient air temperature for operation	15...30 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Ambient air temperature for storage	0...35 °C
Environmental characteristic	Alcohol Acetone Oil UV resistant Bleach Petrol Window-cleaning fluid Ammonia Liquid soap
Environmental health and issues	Halogen free

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0852 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Need no specific recycling operations

### Contractual warranty

Warranty period	18 months
-----------------	-----------