



### Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	Telephone socket
Device application	Communication
Device presentation	Mechanism with fixing frame and central plate
Colour tint	Graphite
Telephone socket type	RJ11 (4 contacts): cat.3 (rate: 16 Mbit/s)

### Complementary

Socket number	2
Number of modules	2 x 1 module
Connections - terminals	Screw terminals (twisted pair)
Marking	Colour coding
Installation direction	Straight
Device mounting	Flush
Fixing mode	Screw For shield : by screw
Material	Fixing frame : zamak Mechanism cover : ABS (acrylonitrile butadiene-styrene)
Depth	23 mm
Width	70.9 mm
Height	70.9 mm
Embedding depth	12 mm
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Market segment	Residential Small commercial

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environment

IP degree of protection	IP20
IK degree of protection	IK01
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0610 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------