Product data sheet Characteristics

MGU50.036.18Z Unica - 1 S.O. (frame) - 2P+E, DE - 2 m - white





Main

IVIAIII		
Range of product	Unica	
Range	Unica	
Device application	Power supply	
Product or component type	Socket-outlet	
Aesthetic name	Unica (standard aesthetic)	
Device presentation	Mechanism with zamak fixing frame	
Socket number	1	
Outlet poles configuration	2P + E	
Outlet standard	German	
Outlet standard description	Side earth	

Complementary

Rated current	16 A, 250 V AC	——of besin
Network frequency	50/60 Hz	pe
Number of modules	2 modules	or
Fixing mode	Long claws	. <u>o</u> .
Colour tint	White	for and
Connections - terminals	Screw terminals	itute .
Cable cross section	04 mm² - cable stiffness: flexible 04 mm² - cable stiffness: rigid	s a substitute for
Minimum load breaking capacity	100 operations 1.25 In and 1.1 Un, cos phi: 0.6	e
Electrical durability	10000 cycles (cos phi: 0.8)	not intended
Insulation resistance	> 5 MOhm @500 V	
Dielectric strength	2000 V	
Material	Mechanism cover : ASA + PC Fixing frame : zamak	documentation
Quantity per set	Film: set of 1	This do
Embedding depth	30 mm	
Depth	40 mm	sclaimer:
		—— ŭ

Width	70.9 mm
Height	70.9 mm
Product weight	0.0739 kg

Environment

Ambient air temperature for operation	1530 °C
Ambient air temperature for storage	035 °C
IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0702 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
	Product environmental	
Product end of life instructions	Need no specific recycling operations	

Contractual warranty

Warranty period	18 months