



### Main

Range	Unica
Range of product	Unica
Aesthetic name	Unica Top - Unica Class
Device application	Control
Product or component type	Switch
Device presentation	Mechanism with zamak fixing frame + long claws
Switch function	1-pole 1-way
Switch application	Bell switch
Colour tint	Graphite

### Complementary

Rated current	10 A, 250 V AC, 50/60 Hz
Electrical durability	40000 cycles (cos phi: 0.6)
Insulation resistance	> 5 MOhm @500 V
Dielectric strength	2000 V
Minimum load breaking capacity	200 operations 1.25 In and 1.1 Un, cos phi: 0.3
Condition of use	Impulse relay control
Opening distance	> 3 mm
Actuator	Push-button
Number of modules	2 modules
Pilot light	Blue neon locator lamp : 1 mA (temperature : 15 °C)
Connections - terminals	Screwless terminals
Cable cross section	0...2.5 mm <sup>2</sup> (rigid) 0...2.5 mm <sup>2</sup> (flexible)
Material	Mechanism cover : ASA + PC Fixing frame : zamak
Marking	Bell symbol
Fixing mode	Long claws
Width	70.9 mm
Height	70.9 mm
Depth	34 mm
Embedding depth	22 mm

Product weight	0.062 kg
Ambient air temperature for operation	25...35 °C
Ambient air temperature for storage	0...50 °C
Standards	EN 60669-1 EMC directive LV directive

## Environment

IP degree of protection	IP20
IK degree of protection	IK01
Environmental characteristic	Oil Bleach Petrol Alcohol UV resistant Window-cleaning fluid Ammonia Acetone Liquid soap
Environmental health and issues	Halogen free

## Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0702 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>

## Contractual warranty

Warranty period	18 months
-----------------	-----------