



Main

Range of product	Unica
Range	Unica
Device application	Control
Product or component type	Switch
Aesthetic name	Unica Top - Unica Class
Device presentation	Mechanism
Switch function	2-way
Switch application	Roller blind
Rated current	10 A, 250 V AC, 50/60 Hz
Actuator	Rocker
Number of modules	2 modules
Fixing mode	Long claws
Cover plate colour tint	Graphite

Complementary

Contacts type and composition	1 C/O
Mechanical interlocking	Interlock between up/down
[Iu] rated interrupted current	Motor : 2.5 A
Opening distance	> 3 mm
Marking	Down UP
Connections - terminals	Screwless terminals
Cable cross section	<= 2.5 mm ² (flexible) <= 2.5 mm ² (rigid)
Minimum load breaking capacity	200 operations 1.25 I _n and 1.1 U _n , cos phi: 0.3
Electrical durability	40000 cycles (cos phi: 0.6)
Insulation resistance	> 5 MOhm @500 V
Dielectric strength	> 2000 V

Material	Fixing frame : zamak Mechanism cover : ABS (acrylonitrile butadiene-styrene)
Standards	EMC directive EN 60669-1 LV directive
Ambient air temperature for operation	25...35 °C
Ambient air temperature for storage	0...50 °C
Embedding depth	22 mm
Depth	34 mm
Width	70.9 mm
Height	70.9 mm
Product weight	0.074 kg

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0621 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------