



Main

Range of product	Unica
Aesthetic name	Unica (standard aesthetic)
Product or component type	Data/Telephone socket
Device presentation	Mechanism with zamak fixing frame + long claws
Telephone socket type	RJ11 (4 contacts): cat.3 (rate: 16 Mbit/s)
Communication network type	Ethernet 1000BASE-T ATM 155 Mbps
Data socket type	RJ45 (8), Cat.5e (transmission rate: <= 100 MHz)
Number of modules	2 modules
Fixing mode	Long claws
Cover plate colour tint	White (RAL 9003)

Complementary

Type of footprint	Infraplus
Connector type	S-One
Cable shielding type	U/UTP
Organization of wire	Unshielded twisted pair
Connections - terminals	Click
Material	Mechanism cover: ASA + PC Fixing frame: zamak
Standards	ISO 8877
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Embedding depth	24.6 mm
Depth	35.8 mm
Width	70.9 mm
Height	70.9 mm
Product weight	0.0647 kg

Environment

IK degree of protection	IK01
IP degree of protection	IP40
Environmental characteristic	Oil Ammonia Bleach UV resistant Alcohol Window-cleaning fluid Liquid soap Petrol Acetone

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0852 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------

Not classified OPS characteristics

Market segment	Residential Small commercial
----------------	---------------------------------