



### Main

|                           |   |
|---------------------------|---|
| Range of product          | Unica   |
| Range                     | Unica   |
| Aesthetic name            | Unica (standard aesthetic)                                    |
| Product or component type | RJ45 connector  |
| Device presentation       | Mechanism with zamak fixing frame + long claws                |
| Colour tint               | White (RAL 9003)  |
| Data socket type          | RJ45 - 8 contacts - category 5e - transmission rate < 155 MHz |
| Provided equipment        | Label holder<br>Protective flap                               |

### Complementary

|                             |  |
|-----------------------------|--|
| Communication network type  | 1000BASE-T   |
| Communication port protocol | ATM 155 Mbps                                       |
| Number of modules           | 2 x 1 modules                                      |
| Socket number               | 2  |
| Type of footprint           | Infraplus  |
| Connector type              | S-One  |
| Cable shielding type        | U/FTP  |
| Organization of wire        | Shielded twisted pair                              |
| Connections - terminals     | Click  |
| Fixing mode                 | Long claws   |
| Material                    | Mechanism cover : ASA + PC<br>Fixing frame : zamak |
| Depth                       | 36 mm  |
| Width                       | 70.9 mm  |
| Height                      | 70.9 mm  |
| Embedding depth             | 25 mm  |
| Product weight              | 0.065 kg   |

|                |                                 |
|----------------|---------------------------------|
| Market segment | Residential<br>Small commercial |
|----------------|---------------------------------|

## Environment

|                                       |  |
|---------------------------------------|--|
| IP degree of protection               | IP40   |
| IK degree of protection               | IK01   |
| Ambient air temperature for operation | 15...30 °C   |
| Ambient air temperature for storage   | 0...35 °C  |
| Environmental characteristic          | Ammonia<br>Liquid soap<br>Oil<br>UV resistant<br>Petrol<br>Window-cleaning fluid<br>Acetone<br>Alcohol<br>Bleach |
| Environmental health and issues       | Halogen free   |
| Standards                             | ISO 8877   |

## Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 0852 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold<br><a href="#">Reference not containing SVHC above the threshold</a>                |
| Product environmental profile    | Available   |
| Product end of life instructions | Need no specific recycling operations   |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|