


Product data sheet

Characteristics

MGU50.2626.12Z

Unica Top/Class - 2 RJ45 socket (S-One) - 2x1 m
- Cat.6, FTP - graph.



Main

Range	Unica
Range of product	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	RJ45 connector
Device presentation	Mechanism with zamak fixing frame + long claws
Colour tint	Graphite
Data socket type	RJ45 - 8 contacts - category 6 - transmission rate < 250 MHz
Provided equipment	Label holder Protective flap

Complementary

Communication network type	1000BASE-TX
Communication port protocol	ATM 1200 Mbps
Number of modules	2 x 1 modules
Socket number	2
Type of footprint	Infraplus
Connector type	S-One
Cable shielding type	U/FTP
Organization of wire	Shielded twisted pair
Connections - terminals	Click
Fixing mode	Long claws
Material	Fixing frame : zamak Mechanism cover : ABS (acrylonitrile butadiene-styrene)
Depth	36 mm
Width	70.9 mm
Height	70.9 mm
Embedding depth	25 mm
Product weight	0.098 kg

Environment

IP degree of protection	IP40
-------------------------	------

MGU50.2626

IK degree of protection	IK01
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Environmental characteristic	Oil Petrol UV resistant Alcohol Bleach Ammonia Liquid soap Acetone Window-cleaning fluid
Environmental health and issues	Halogen free
Standards	ISO 8877

Contractual warranty

Warranty period	18 months
-----------------	-----------