



### Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	Key card switch
Device application	Control
Device presentation	Mechanism with zamak fixing frame + long claws
Cover plate colour tint	Graphite

### Complementary

[Ue] rated operational voltage	230 V +/- 10 % AC 50 Hz
Rated current	10 A
Load type	230 V AC incandescent lamp - 1470 W 230 V AC halogen lamp - 1470 W 230 V AC fan - 1470 W 230 V AC convector - 1470 W Low voltage halogen lamp with ferromagnetic transformer - 1000 VA Low voltage halogen lamp with electronic transformer - 1470 VA Fluorescent tube ferromagnetic ballast - 1470 VA Compact fluorescent lamp - 1470 W LED lamp - 1470 W Contactor
Condition of use	Control through appropriate relay
Actuator	Card 54 x 86 x 0.85 mm (maximum)
Number of modules	2 modules
Fuse type	Electronic
Maximum number of switchings	50000 operations
Pilot light	Locator lamp
Marking	Vertical insertion pictogram
Connections - terminals	Soldered connectors
Clamping connection capacity	<= 1 x 2.5 mm <sup>2</sup> for flexible cable(s)

	<= 1 x 2.5 mm <sup>2</sup> for rigid cable(s)
Fixing mode	Long claws
Material	Mechanism cover : ASA + PC Fixing frame : zamak
Embedding depth	14 mm
Depth	Unica Top cover frame : 35 mm Unica Class cover frame : 35 mm
Width	70.9 mm
Height	70.9 mm
Product weight	0.0689 kg

## Environment

IP degree of protection	IP20
IK degree of protection	IK01
Ambient air temperature for operation	5...30 °C
Ambient air temperature for storage	-20...60 °C
Environmental characteristic	Window-cleaning fluid UV resistant Acetone Bleach Alcohol Oil Petrol Liquid soap Ammonia
Environmental health and issues	Halogen free
Standards	EN 61058-1

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0621 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------