



Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	RJ45 connector
Device presentation	Mechanism with zamak fixing frame + long claws
Colour tint	Graphite
Data socket type	RJ45 - 8 contacts - category 6 - transmission rate < 250 MHz
Provided equipment	Protective flap Label holder

Complementary

Communication network type	1000BASE-TX
Communication port protocol	ATM 1200 Mbps
Number of modules	2 modules
Socket number	1
Type of footprint	Infraplus
Connector type	S-One
Cable shielding type	U/UTP
Organization of wire	Unshielded twisted pair
Connections - terminals	Click
Fixing mode	Long claws
Material	Fixing frame : zamak Mechanism cover : ABS (acrylonitrile butadiene-styrene)
Depth	36 mm
Width	70.9 mm
Height	70.9 mm
Embedding depth	25 mm
Product weight	0.066 kg

Environment

IP degree of protection	IP40
IK degree of protection	IK01
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Environmental characteristic	Bleach UV resistant Acetone Petrol Alcohol Oil Window-cleaning fluid Ammonia Liquid soap
Environmental health and issues	Halogen free
Standards	ISO 8877

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0852 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------