



Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	R-TV/SAT socket
Device presentation	Mechanism with zamak fixing frame + long claws
TV socket type	Individual socket
Colour tint	Graphite

Complementary

TV connector	Male IEC 9.52 mm
SAT connector	Female IEC 9.52 mm
Path attenuation	R : < 0.8 dB @10...108 MHz TV/UHF : < 0.8 dB @470...830 MHz TV/VHF : < 0.8 dB @118...470 MHz SAT : < 1.4 dB @950...2400 MHz
DC current flow	In SAT socket
Number per line	1
Number of modules	2 modules
Material	Mechanism cover : ASA + PC Fixing frame : zamak
Condition of use	Parallel distribution systems
Fixing mode	Long claws
Depth	28 mm
Width	70.9 mm
Height	70.9 mm
Embedding depth	18 mm
Product weight	0.112 kg

MGU50.454

Environment

IP degree of protection	IP20
IK degree of protection	IK01
Ambient air temperature for operation	15...35 °C
Ambient air temperature for storage	0...35 °C
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free
Standards	DIN 45325 DIN 45330 EMC directive EN 50083-1 EN 50083-2 EN 50083-4 R.D. 1/1998 R.D. 279/1999 UNE 20-523-79 (2e)

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0702 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------