



## Main

Range	Unica
Range of product	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	R-TV/SAT socket
Device presentation	Mechanism with zamak fixing frame + long claws
TV socket type	End-of-line (terminal socket)
Colour tint	Graphite

## Complementary

TV connector	Male IEC 9.52 mm
SAT connector	Female IEC 9.52 mm
Path attenuation	R : < 9 dB @10...108 MHz TV/UHF : < 9 dB @470...830 MHz TV/VHF : < 9 dB @118...470 MHz SAT : < 17 dB @950...2400 MHz
DC current flow	In SAT socket
Number per line	1
Number of modules	2 modules
Material	Mechanism cover : ASA + PC Fixing frame : zamak
Condition of use	Series distribution systems
Fixing mode	Long claws
Depth	28 mm
Width	70.9 mm
Height	70.9 mm
Embedding depth	18 mm
Product weight	0.112 kg

MGU50.455

## Environment

IP degree of protection	IP20
IK degree of protection	IK01
Ambient air temperature for operation	15...35 °C
Ambient air temperature for storage	0...35 °C
Environmental characteristic	Petrol Bleach Ammonia Oil Acetone Alcohol UV resistant Window-cleaning fluid Liquid soap
Environmental health and issues	Halogen free
Standards	EN 50083-2 R.D. 279/1999 DIN 45330 UNE 20-523-79 (2e) DIN 45325 EMC directive EN 50083-1 EN 50083-4 R.D. 1/1998

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0000 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------