



Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica (standard aesthetic)
Product or component type	TV socket
Device presentation	Mechanism with zamak fixing frame + long claws
TV socket type	Male passage
Colour tint	White

Complementary

TV connector	Male IEC 9.52 mm
Branch attenuation	TV : 0.5 dB
Path attenuation	TV : 11 dB @5...2150 MHz
DC current flow	No
Number per line	4
Number of modules	2 modules
Material	Mechanism cover : ASA + PC Fixing frame : zamak
Fixing mode	Long claws
Depth	28 mm
Width	70.9 mm
Height	70.9 mm
Embedding depth	18 mm
Product weight	0.112 kg

Environment

IP degree of protection	IP20
IK degree of protection	IK01

MGU50.463

Ambient air temperature for operation	15...35 °C
Ambient air temperature for storage	0...35 °C
Environmental characteristic	Oil Ammonia UV resistant Bleach Window-cleaning fluid Petrol Acetone Liquid soap Alcohol
Environmental health and issues	Halogen free
Standards	EMC directive EN 50083-2 EN 50083-1 EN 50083-4

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0702 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------