



Main

Range	Unica
Range of product	Unica
Aesthetic name	Unica (standard aesthetic)
Product or component type	Telephone socket
Device presentation	Mechanism with zamak fixing frame + long claws
Colour tint	White
Telephone socket type	RJ12 (6 contacts): cat.3 (rate: 16 Mbit/s)

Complementary

Socket number	1
Number of modules	2 modules
Connections - terminals	Screwless terminals (twisted pair)
Fixing mode	Long claws
Material	Mechanism cover : ASA + PC Fixing frame : zamak
Depth	36 mm
Width	45 mm
Height	45 mm
Embedding depth	26 mm
Product weight	0.052 kg
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Market segment	Small commercial Residential

Environment

IP degree of protection	IP20
-------------------------	------

MGU50.493

IK degree of protection	IK01
Environmental characteristic	Bleach Window-cleaning fluid Acetone Oil Liquid soap Alcohol UV resistant Petrol Ammonia
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0852 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------