



Main

| | |
|--------------------------------|--|
| Range of product | Unica |
| Aesthetic name | Unica Top - Unica Class |
| Product or component type | Rotary dimmer |
| Device presentation | Mechanism with zamak fixing frame + long claws |
| Fixing mode | Long claws |
| Dimmer application | Inductive load Resistive load |
| [Ue] rated operational voltage | 230 V AC, 50 Hz |
| Number of modules | 2 modules |
| Cover plate colour tint | Graphite |

Complementary

| | |
|------------------------------|--|
| Dimmer control | 270° rotary setting ON/OFF push |
| Maximum permanent current | 1.74 A |
| Total number of wires | 2 |
| Load type | 230 V AC halogen lamp - 40...400 W 230 V AC incandescent lamp - 40...400 W Low voltage halogen lamp with ferromagnetic transformer - 40...400 VA |
| Protection type | Fuse protection |
| Fuse type | 4 Ah (5 x 20 mm) @230 V 50 Hz |
| Marking | L+N |
| Connections - terminals | Screw terminals |
| Clamping connection capacity | <= 2 x 2.5 mm ² for flexible cable(s) <= 2 x 2.5 mm ² for rigid cable(s) |
| Connected auxiliaries | 2-way switch |
| Material | Mechanism cover : ASA + PC Fixing frame : zamak |
| Standards | EN 60669-2-1 |

| | |
|---------------------------------------|-------------|
| Product certifications | CE |
| Ambient air temperature for operation | 5...30 °C |
| Ambient air temperature for storage | -20...60 °C |
| Embedding depth | 34 mm |
| Depth | 54 mm |
| Width | 70.9 mm |
| Height | 70.9 mm |
| Product weight | 0.1099 kg |

Environment

| | |
|---------------------------------|--|
| IK degree of protection | IK01 |
| IP degree of protection | IP20 |
| Environmental characteristic | Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid |
| Environmental health and issues | Halogen free |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0805 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference contains SVHC above the threshold - Go to CaP for more details Go to CaP for more details |
| Product environmental profile | Available |
| Product end of life instructions | Available |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|