

## Product data sheet

### Characteristics

# MGU50.530.12

Unica KNX - push-button - 2-way - 10 A 24 V DC -  
2 m - graph.



### Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica KNX
Device application	Control
Product or component type	Switch
Device presentation	Mechanism with zamak fixing frame
Switch function	1-pole 2-way
Colour tint	Graphite

### Complementary

Rated current	10 A, 24 V DC
Insulation resistance	> 5 MOhm @500 V
Dielectric strength	2000 V
Actuator	Push-button
Number of modules	2 modules
Pilot light	Blue LED : 1 mA (temperature : 15 °C)
Connections - terminals	Screwless terminals
Cable cross section	0...2.5 mm <sup>2</sup> (rigid) 0...2.5 mm <sup>2</sup> (flexible)
Fixing mode	Long claws
Depth	38 mm
Embedding depth	13 mm
Ambient air temperature for operation	-5...45 °C
Standards	EN 60669-1 EMC directive LV directive

### Environment

IP degree of protection	IP20
Environmental characteristic	Liquid soap Ammonia Oil Petrol

UV resistant  
Acetone  
Window-cleaning fluid  
Alcohol  
Bleach

---

Environmental health and issues      Halogen free

---

### Offer Sustainability

---

RoHS (date code: YYWW)      Compliant - since 1016 - Schneider Electric declaration of conformity  
[Schneider Electric declaration of conformity](#)

---

REACH      Reference not containing SVHC above the threshold  
[Reference not containing SVHC above the threshold](#)

---

### Contractual warranty

---

Warranty period      18 months

---