



Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica KNX
Product or component type	Switch
Device application	Control
Device presentation	Mechanism with zamak fixing frame + long claws
Cover plate colour tint	Graphite

Complementary

Rated current	10 A, 250 V AC, 50/60 Hz
Insulation resistance	> 5 MOhm @500 V
Dielectric strength	> 2000 V
Number of modules	2 modules
Switch function	2-way
Contacts type and composition	2 NO
Opening distance	> 3 mm
Transmission support medium	Infrared
Actuator	Push-button
Pilot light	Blue LED : 1 mA (temperature : 15 °C)
Connections - terminals	Screwless terminals
Cable cross section	<= 2.5 mm ² (flexible) <= 2.5 mm ² (rigid)
Fixing mode	Claws

Environment

IP degree of protection	IP20
IK degree of protection	IK01
Ambient air temperature for operation	-5...45 °C
Environmental characteristic	UV resistant Bleach Acetone Oil

Petrol
Ammonia
Liquid soap
Window-cleaning fluid
Alcohol

Environmental health and issues Halogen free

Standards LV directive
EMC directive

Offer Sustainability

RoHS (date code: YYWW) Compliant - since 1016 - Schneider Electric declaration of conformity

 [Schneider Electric declaration of conformity](#)

REACH Reference not containing SVHC above the threshold
[Reference not containing SVHC above the threshold](#)

Contractual warranty

Warranty period 18 months
