



### Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica KNX
Product or component type	Movement detector
Device presentation	Mechanism with zamak fixing frame + long claws
Cover plate colour tint	Graphite

### Complementary

[Ue] rated operational voltage	230 V AC (+/- 10 %), 50/60 Hz
Movement detection area	9 x 9 m (PIR mounting height 2.15m)
Detection angle	Full 180°
Number of modules	2 modules
Light intensity adjustment	10...< 1000 lux @rotary switch 10...2000 lux @ETS
Time delay range	1 s...8 min for rotary switch 1 s...255 h for ETS
Clamping connection capacity	<= 2 x 2.5 mm <sup>2</sup> for flexible cable(s) <= 2 x 2.5 mm <sup>2</sup> for rigid cable(s)
Connections - terminals	Screwless terminals
Material	Mechanism cover : ASA + PC Fixing frame : zamak
Fixing mode	Long claws
Mounting height	1...2.5 m
Depth	56 mm
Embedding depth	34 mm

### Environment

IP degree of protection	IP20
Ambient air temperature for operation	-5...45 °C
Environmental characteristic	Acetone Alcohol Ammonia Bleach

	Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free
Standards	EMC directive LV directive

### Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0852 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
------------------------	---

### Contractual warranty

Warranty period	18 months
-----------------	-----------