



Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica KNX
Product or component type	Room temperature control unit
Device presentation	Mechanism with zamak fixing frame + long claws
Colour tint	Graphite

Complementary

[Ue] rated operational voltage	230 V AC (+/- 10 %), 50/60 Hz
Number of modules	2 modules
Device composition	4 buttons Display
Clamping connection capacity	<= 2 x 2.5 mm ² for flexible cable(s) <= 2 x 2.5 mm ² for rigid cable(s)
Contacts type and composition	1 C/O
Connections - terminals	Screwless terminals
Information displayed	Temperature Time Operating mode Day
Status LED	Programming LED
Programmable temperature	No
Temperature setting range	0...40 °C
Measurement accuracy	± 1 K
Fixing mode	Long claws
Mounting height	> 1.5 m
Depth	39 mm
Embedding depth	26 mm

Environment

IP degree of protection	IP20
IK degree of protection	IK01

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient air temperature for operation	-5...45 °C
Environmental characteristic	UV resistant Liquid soap Oil Bleach Window-cleaning fluid Ammonia Alcohol Acetone Petrol
Environmental health and issues	Halogen free
Standards	EMC directive LV directive

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0852 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
------------------------	---

Contractual warranty

Warranty period	18 months
-----------------	-----------