



Main

Range	Unica
Range of product	Unica
Aesthetic name	Unica Top - Unica Class
Device application	Control
Product or component type	Selector switch
Device presentation	Mechanism with zamak fixing frame + long claws
Switch function	4 positions
Colour tint	Graphite

Complementary

Rated current	32 A, 250 V AC, 50/60 Hz
Power range	40...300 VA 40...300 W
Electrical durability	10000 cycles (cos phi: 0.6)
Insulation resistance	> 5 MOhm @500 V
Dielectric strength	2000 V
Minimum load breaking capacity	200 operations 1.25 In and 1.1 Un, cos phi: 0.3
Opening distance	> 3 mm
Actuator	Rotary
Number of modules	2 modules
Connections - terminals	Screw terminals
Cable cross section	0...6 mm ² (flexible) 0...6 mm ² (rigid)
Material	Fixing frame : zamak Mechanism cover : ABS (acrylonitrile butadiene-styrene)
Marking	1
Fixing mode	Long claws
Width	70.9 mm

Height	70.9 mm
Depth	30 mm
Product weight	0.076 kg
Ambient air temperature for operation	25...35 °C
Ambient air temperature for storage	0...50 °C
Standards	EMC directive EN 60669-1 LV directive

Environment

IP degree of protection	IP20
IK degree of protection	IK01
Environmental characteristic	Acetone Petrol Alcohol UV resistant Liquid soap Window-cleaning fluid Oil Ammonia Bleach
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0805 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------