



Main

Range	Unica
Aesthetic name	Unica
Product or component type	Emergency light
Device presentation	Mechanism with zamak fixing frame
[Ue] rated operational voltage	230 V AC (+/- 10 %), 50 Hz
Number of modules	2 modules
Fixing mode	Clip-in

Complementary

Condition of use	Battery and bulb cannot be replaced
Light block colour	Green
Bulb type	LED
Bulb lifespan	400 h
Illuminance	45 lux 25 cm
Connections - terminals	Screw terminals
Clamping connection capacity	<= 2 x 2.5 mm ² for flexible cable(s) <= 2 x 2.5 mm ² for rigid cable(s)
Charging time	24 h
Electrical durability	500 cycles
Material	Fixing frame : zamak Mechanism cover : transparent plastic
Standards	EN 60598-2-22 EMC directive UNE 60598-2-22 UNE 20062-93 LV directive
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Embedding depth	33 mm
Depth	44 mm
Width	45 mm
Height	45 mm
Market segment	Small commercial

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

IP degree of protection	IP20
Environmental characteristic	Liquid soap Bleach Window-cleaning fluid Acetone Oil Alcohol Petrol UV resistant Ammonia
Environmental health and issues	Halogen free

Contractual warranty

Warranty period	18 months
-----------------	-----------
