



Main

Range of product	Unica
Range	Unica
Device application	Signalling
Product or component type	Buzzer
Aesthetic name	Unica Top - Unica Class
Device presentation	Mechanism with zamak fixing frame + long claws
[Ue] rated operational voltage	230 V AC, 50/60 Hz
Number of modules	2 modules
Fixing mode	Long claws
Colour tint	Graphite

Complementary

Current consumption	40 mA
Type of setting	Volume can be adjusted using a screw
Operating time	0...60 ms
Connections - terminals	Screw terminals
Acoustic level	Between 76 and 80 dB
Cable cross section	0.75...1.5 mm ² (flexible) 0.75...1.5 mm ² (rigid)
Material	Mechanism cover : ASA + PC Fixing frame : zamak
Standards	EMC directive LV directive
Product certifications	CE
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Embedding depth	31 mm
Depth	42 mm
Width	45 mm
Height	45 mm
Product weight	0.083 kg

MGU50.785

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0805 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------