

Product data sheet

Characteristics

MGU50.786.12Z

Unica Top/Class - electronic bell - 230V AC - 2 m
- long claws - graphite



Main

Range of product	Unica
Range	Unica
Device application	Signalling
Product or component type	Electronic bell
Aesthetic name	Unica Top - Unica Class
Device presentation	Mechanism with zamak fixing frame + long claws
[Ue] rated operational voltage	230 V AC, 50/60 Hz
Number of modules	2 modules
Fixing mode	Long claws
Colour tint	Graphite

Complementary

Current consumption	14 mA
Type of setting	5 programmable melodies
Connections - terminals	Screw terminals
Acoustic level	70 dB/1m
Cable cross section	0.75...1.5 mm ² (flexible) 0.75...1.5 mm ² (rigid)
Connected auxiliaries	10 standard push-buttons connected in parallel 3 indicator lights connected in parallel
Material	Mechanism cover : ASA + PC Fixing frame : zamak
Standards	IEC 62080
Product certifications	CE
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Embedding depth	33 mm
Depth	44 mm
Width	45 mm
Height	45 mm
Product weight	0.15 kg

MGU50.786

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Oil Ammonia Acetone Window-cleaning fluid Bleach Petrol Liquid soap Alcohol UV resistant
Environmental health and issues	Halogen free

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0852 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------