



Main

Range of product	Unica
Range	Unica
Device application	Mounting
Product or component type	Cover frame
Aesthetic name	Unica Plus
Number of gangs	2 gangs vertical
Fixing mode	Clip-in
Cover frame colour tint	White
Decoration colour	White

Complementary

Material	ASA + PC cover frame ASA + PC intermediate part Zamak cover frame
Standards	EN 60669-1
Height	147 mm
Width	80 mm
Depth	14 mm
Distance between centers	57 mm
Product weight	0.029 kg

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Alcohol Ammonia Bleach Liquid soap Oil Acetone Petrol

MGU6.014V

Window-cleaning fluid
UV resistant

Environmental health and issues	Halogen free
---------------------------------	--------------

Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

RoHS (date code: YYWW)	Compliant - since 0852 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
------------------------	---

REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
-------	--

Product environmental profile	Available Product environmental
-------------------------------	--

Product end of life instructions	Need no specific recycling operations
----------------------------------	---------------------------------------

Contractual warranty

Warranty period	18 months
-----------------	-----------
