



Main

Range of product	Unica
Range	Unica
Device application	Mounting
Product or component type	Cover frame
Aesthetic name	Unica Plus
Number of gangs	1 gang
Number of modules	2 modules
Fixing mode	Without claws
Colour tint	White

Complementary

Provided equipment	Fixing frame
Material	Cover frame : ASA + PC Intermediate fixing frame : ASA + PC
Standards	EN 60669-1
Width	80 mm
Height	90 mm
Depth	30 mm
Product weight	0.052 kg
Market segment	Residential Small commercial

Environment

IK degree of protection	IK01
IP degree of protection	IP44
Environmental characteristic	Acetone Alcohol Ammonia Bleach

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Liquid soap
Oil
Petrol
UV resistant
Window-cleaning fluid

Environmental health and issues	Halogen free
---------------------------------	--------------

Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

RoHS (date code: YYWW)	Compliant - since 0702 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
------------------------	---

REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
-------	--

Product environmental profile	Available Product environmental
-------------------------------	--

Product end of life instructions	Need no specific recycling operations
----------------------------------	---------------------------------------

Contractual warranty

Warranty period	18 months
-----------------	-----------
