



Main

Range of product	Unica
Range	Unica
Device application	Mounting
Product or component type	Cover frame
Aesthetic name	Unica Top
Number of gangs	1 gang
Fixing mode	Clip-in
Cover frame colour tint	Cherry tree
Decoration colour	Aluminium

Complementary

Material	ASA + PC decorative frame ASA + PC intermediate part Zamak cover frame
Standards	EN 60669-1
Height	80 mm
Width	90 mm
Depth	14 mm
Product weight	0.054 kg
Market segment	Small commercial Residential

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Bleach UV resistant Petrol Window-cleaning fluid

MGU66.002-0M2

Oil
Alcohol
Ammonia
Liquid soap
Acetone

Environmental health and issues	Halogen free
---------------------------------	--------------

Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

RoHS (date code: YYWW)	Compliant - since 0610 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
------------------------	---

REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
-------	--

Product environmental profile	Available Product environmental
-------------------------------	--

Product end of life instructions	Need no specific recycling operations
----------------------------------	---------------------------------------

Contractual warranty

Warranty period	18 months
-----------------	-----------
