



Main

Range of product	Unica
Range	Unica
Device application	Mounting
Product or component type	Cover frame
Aesthetic name	Unica Top
Number of gangs	3 gangs horizontal
Fixing mode	Clip-in
Cover frame colour tint	Bright chrome
Decoration colour	Aluminium

Complementary

Material	ASA + PC decorative frame
Standards	EN 60669-1
Height	80 mm
Width	232 mm
Depth	14 mm
Distance between centers	71 mm
Product weight	0.118 kg
Market segment	Residential Small commercial

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap

Oil
Petrol
UV resistant
Window-cleaning fluid

Environmental health and issues	Halogen free
---------------------------------	--------------

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0610 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------
