



Main

Range of product	Unica
Range	Unica
Device application	Mounting
Product or component type	Cover frame
Aesthetic name	Unica Top
Number of gangs	4 gangs horizontal
Fixing mode	Clip-in
Cover frame colour tint	Bright chrome
Decoration colour	Aluminium

Complementary

Material	ASA + PC decorative frame ASA + PC intermediate part Zamak cover frame
Standards	EN 60669-1
Height	80 mm
Width	303 mm
Depth	14 mm
Distance between centers	71 mm
Product weight	0.16 kg
Market segment	Residential Small commercial

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Alcohol Acetone Oil

Liquid soap
Window-cleaning fluid
Petrol
Bleach
UV resistant
Ammonia

Environmental health and issues

Halogen free

Offer Sustainability

Sustainable offer status

Green Premium product

RoHS (date code: YYWW)

Compliant - since 0610 - Schneider Electric declaration of conformity

 [Schneider Electric declaration of conformity](#)

REACH

Reference not containing SVHC above the threshold

[Reference not containing SVHC above the threshold](#)

Product environmental profile

Available

 [Product environmental](#)

Product end of life instructions

Need no specific recycling operations

Contractual warranty

Warranty period

18 months
