



Main

Range of product	Unica
Range	Unica
Device application	Mounting
Product or component type	Cover frame
Aesthetic name	Unica Top
Number of gangs	2 gangs vertical
Fixing mode	Clip-in
Cover frame colour tint	Bright chrome
Decoration colour	Aluminium

Complementary

Material	ASA + PC intermediate part Zamak cover frame
Standards	EN 60669-1
Height	147 mm
Width	80 mm
Depth	14 mm
Distance between centers	57 mm
Product weight	0.078 kg

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	UV resistant Acetone Window-cleaning fluid Ammonia Alcohol Bleach

MGU66.014V

Oil
Petrol
Liquid soap

Environmental health and issues	Halogen free
---------------------------------	--------------

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0852 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------
