



### Main

Range of product	Unica
Range	Unica
Device application	Mounting
Product or component type	Cover frame
Aesthetic name	Unica Class
Number of gangs	1 gang
Fixing mode	Clip-in
Cover frame colour tint	Ice aluminium

### Complementary

Material	Aluminium cover frame ASA + PC decorative frame
Standards	EN 60669-1
Height	93 mm
Width	102 mm
Depth	11 mm
Distance between centers	71 mm
Product weight	0.1 kg
Market segment	Residential Small commercial

### Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap

MGU68.002

Oil  
Petrol  
UV resistant  
Window-cleaning fluid

Environmental health and issues

Halogen free

### Offer Sustainability

Sustainable offer status

Green Premium product

RoHS (date code: YYWW)

Compliant - since 0852 - Schneider Electric declaration of conformity

 [Schneider Electric declaration of conformity](#)

REACH

Reference not containing SVHC above the threshold

[Reference not containing SVHC above the threshold](#)

Product environmental profile

Available

 [Product environmental](#)

Product end of life instructions

Need no specific recycling operations

 [Product environmental](#)

### Contractual warranty

Warranty period

18 months