



Main

Range of product	Unica
Range	Unica
Device application	Mounting
Product or component type	Cover frame
Aesthetic name	Unica Class
Number of gangs	3 gangs horizontal 3 gangs vertical
Fixing mode	Clip-in
Cover frame colour tint	Ice aluminium

Complementary

Material	Aluminium cover frame ASA + PC intermediate part Zamak cover frame
Standards	EN 60669-1
Height	93 mm
Width	244 mm
Depth	11 mm
Distance between centers	71 mm
Product weight	0.236 kg
Market segment	Residential Small commercial

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Acetone Alcohol Ammonia

Bleach
Liquid soap
Oil
Petrol
UV resistant
Window-cleaning fluid

Environmental health and issues

Halogen free

Offer Sustainability

Sustainable offer status

Green Premium product

RoHS (date code: YYWW)

Compliant - since 0852 - Schneider Electric declaration of conformity

 [Schneider Electric declaration of conformity](#)

REACH

Reference not containing SVHC above the threshold

[Reference not containing SVHC above the threshold](#)

Product environmental profile

Available

 [Product environmental](#)

Product end of life instructions

Need no specific recycling operations

Contractual warranty

Warranty period

18 months
