



### Main

Range	Unica
Product or component type	Audio receiver
Device presentation	Mechanism with central plate

### Complementary

Device mounting	Flush
Fixing mode	Screws Claws
Device composition	1 audio receiver 1 power supply
Communication network type	Bluetooth (10 m)
Connector type	Jack (3.5 mm, 62 Ohm)
Colour tint	Graphite
[Ue] rated operational voltage	Audio receiver 15/16 V DC Power supply 265 V AC 47...63 Hz
Current consumption	4.5...100 mA with bluetooth 4.5...75 mA with jack
Power consumption in W	12 W (power supply)
Input voltage	100 mVrms with jack
Output voltage	15 V DC (power supply)
Output current	800 mA (power supply)
Nominal output power	5 W 2.5 W 1.5 W 0 W
Signal isolation	58 dB
Bandwidth	45...20000 Hz
Signal to noise ratio	84 dB
Number of addresses	0...9999
Transmission frequency	2.4 GHz
Radio power	7 dBm
Connections - terminals	Screw terminals
Material	ABS (acrylonitrile butadiene-styrene) centre plate

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

---

Product weight	0.24 kg
----------------	---------

---

## Environment

---

IP degree of protection	IP20
-------------------------	------

---