



Main

Range of product	Unica
Range	Unica
Device application	Mounting
Product or component type	Mounting box for mechanism
Aesthetic name	Unica Colors Unica Basic
Number of modules	4 modules
Number of gangs	2 gangs
Fixing mode	By 4 pins
Additional information	Flame resistance 650 °C-30 s Self-extinguishing materials
Box colour tint	White

Complementary

Wiring device mounting	Surface
Cable entry	4 knock-outs
Product compatibility	For universal fixing frame
Material	ASA + PC for box
Depth	35 mm
Width	156 mm
Height	80 mm
Product weight	0.086 kg
Market segment	Residential Small commercial

Environment

Standards	RoHS compliant UNE 60670-1
-----------	-------------------------------

MGU8.004

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Petrol Window-cleaning fluid Ammonia Alcohol Acetone Bleach Liquid soap Oil UV resistant

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0624 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------